



Go green. \$ave some green.

HiLine Series XG™ Electric Vehicles

XG™

4-Passenger Low-Speed Vehicle

Today's educated consumer wants the perfect combination of technology, safety and convenience while having peace of mind that they are doing their part to improve the environment... at a price they can afford.

Introducing the HiLine XG™ Series.


Classified as a "low-speed vehicle" (LSV) or "neighborhood electric vehicle" (NEV), the HiLine XG™ has been certified for use in most states on roads with a posted speed limit of 35mph or less, as it has a maximum speed of 25mph.



Standard Features

- Maintenance-free batteries
- Easy-to-read digital console with 12V accessory outlet
- Sony AM/FM stereo system with CD player
- Enclosed cargo carrier with security lock
- High-low beam quartz halogen headlamps
- Interior dome light, cup holders, scuff guards, grab handles and floor mats
- Ergonomic, easy-to-clean molded-foam vinyl seating
- Integrated individual padded head restraints
- Adjustable driver, rearview and passenger mirrors
- Front and rear brake lights, turn signals, back-up alarm and hazard lights
- Standard U.S. automotive 3-point strap safety belts
- Tinted automotive safety windshield glass with wiper
- Rack-and-pinion steering for improved control
- Convenient onboard 48-volt DC charging dock for use in any standard 110-volt AC 15-amp outlet
- Dual front independent suspension with coil over double-action shock absorber for a smoother ride
- Each vehicle is thoroughly tested for quality and certified to meet and exceed all FMVSS standards

HiLine XG-4™ Specifications	
Range	Up to 50 miles*
Batteries	48VDC (8 x 6-volt batteries)
Charging Time	Using a standard 110-volt, 15-amp outlet: <ul style="list-style-type: none"> • 80% recharged in 8 to 10 hours • 100% recharged in 12 hours
Speed	<ul style="list-style-type: none"> • Transition switch allows driver to select 17mph (golf course path) or 25mph (road) • Top speed is 25mph, according to FMVSS 500 for LSV/NEV/ZEV
Curb Weight	1,763 lbs
GVWR	2,530 lbs
Payload Capacity**	920 lbs
Configuration	4-Passenger
Dimensions (HxWxL)	70"H x 60"W x 134"L
Wheelbase	102"
Turning Circle	32 ft.
Tires	Street-rated, 13-inch steel radial tubeless tires
Body	<ul style="list-style-type: none"> • All-steel frame with rust protection primer and plastic coating • Fiberglass body panels • Front and rear bumpers
Propulsion	<ul style="list-style-type: none"> • Front wheel drive • Heavy-duty 5.8HP DC motor • Curtis 1268 controller with voltage self-check
Braking System	<ul style="list-style-type: none"> • Double-circuit, full hydraulic, front-wheel disc, rear-wheel drum, regenerative braking system for optimum driving range and safety • Parking brake for inclines
*Range will vary depending on terrain, driving style and/or vehicle payload.	
**Options + passengers + cargo	



HiLine Carts & Cars Inc.

P.O. Box 72660, Newnan, GA 30271 USA

Phone: 770.783.2797 Fax: 866.927.9966

www.xgreencars.com e: sales@xgreencars.com

HiLine Carts & Cars Inc. reserves the right to change specifications, components and suppliers at any time without giving notice.